Technical specifications

Cambridge Audio

S-Series S70 speaker

- Woven heat-blocked polyfibre cone offering lightweight rigidity for dynamic bass and faithful midrange
- Rigid phase plug for improved off-axis integration
- High quality rubber surround edge, profiled for superior, reliable cone termination
- High flux density, self shielding neodymium magnet assemblies offer improved sensitivity and better dynamics than conventional tweeter magnets.
- Optimised magnet motor assembly for extended lower frequencies from efficient enclosure tuning
- Soft dome tweeter for high efficiency, smooth and accurate high frequencies
- Rigid MDF cabinet with internal cross-bracing
- High quality laminate core inductors giving cleaner bass with improved dynamics, polypropylene film capacitors in critical path giving high resolution image
- Available in Noir or Dark Oak finishes

Detailed Specifications

Sensitivity	90dB
Frequency response	39Hz – 20kHz
Impedance	8 Ohms compatible
Recommended max. Amp power	120 Watts
Drivers	Tweeter: 1 x 25mm (1”) Woofer: 2 x 130mm (5") mid/bass driver
Crossover	2nd Order 2.5 way
Ported	1 rear
Magnetic shielding	Yes
Dimensions (H x W x D)	without plinth 910 x 160 x 240mm (35.8 x 6.3 x 9.4’’) without grill with plinth 938 x 230 x 305mm (36.9 x 9.05 x 12”) without grill
Weight	12.4kg (27.3lbs)

© Cambridge Audio 2010

Cambridge Audio is a brand of Audio Partnership Plc,
Registered Office: Gallery Court, Hankey Place, London SE1 4BB,
United Kingdom. Registered in England No. 2953313

www.cambridge-audio.com

Cambridge Audio’s policy is one of continuous improvement.
Design and specifications are therefore subject to change without prior notice